



Global Security Systems Co W.L.L.

Hawally - 32030, Kuwait.

Tel. 00965-22644052

Fax: 00965-22644057

www.globalsecuritysys.com

E-mail: info@globalsecuritysys.com

www.facebook.com/gsskuwait

www.twitter.com/gssku

TEMP°ALERT® TA-1

Mechanical Temperature Monitor with Single Output

- Connects to new and existing alarm systems.
- No power required to operate.
- Sleek, low-profile styling.
- Normally open (N.O.)
- Do not put console in freezer/cooler. Use an EnviroAlert with a wired probe.



Warehouse



Basement



Agriculture



Server Room



Industry



Remote Home

Specifications:

Power Requirements:	No power required to operate.
Low Limit Adjust Range:	-30° to 120° F (-34° to 49° C) Non-condensing environment.
High Limit Adjust Range:	-20° to 130° F (-29° to 54° C) Non-condensing environment.
Minimum Temp Span:	10° Recommended distance between high and low set points.
Temp Accuracy:	±3° F (±1.7° C)
Temp Response Time:	TC = 14 minutes
Outputs:	Gold plated N.O. dry contacts. Not for high voltage use.
Contact Output Rating:	12VDC @ 50mA
Weight:	6.5 oz (0.18 kg)
Dimensions:	6.25 x 3.75 x 2" (15.9 x 9.5 x 5.1 cm)
Mounting:	Key slot