

# GNS-18412, GNS-116412

8/16CH Built-in PoE Network Video Recorder



## Key Features

- Real-Time Full HD Recording and Up to 5MP Recording
- Built-in PoE Switch(IEEE 802.3af/at Support)
- Compatible with Onvif Supporting Cameras
- Full HD Display(VGA, HDMI)
- Built-in Discovery
- Internal 4 HDD
- Built-in DVD RW, Front Button and Jog&Shuttle(HNR-8410/HNR-16410)
- 1EAXe-SATA, 2EAXUSB2.0, iSCSI support
- Alarm Input(8/16), Alarm Output(8/16)
- 48VDC

## Technical Specifications

Model		GNS-18412	GNS-116412
IP Camera Input	Input	8xRJ45	16xRJ45
	Embedded PoE Switch		IEEE 802.3af/at
	Resolution		VGA/D1/960H/960p/1080p/3M/5M
Monitor Output	Protocol		Onvif v2.3 Base
	HD Video Output		VGA, HDMI
	Main Video Resolution		Up to 1920x1080p
	Screen Split Mode	1/4/6/8/9	1/4/6/8/9/13/16
	PIP and Zoom		PIP/Zoom(x2, x4, x6, x8)
Pentaplex Mode	Audio Output		1xRCA
	Mobile Phone Support		Simultaneous Live, Recording, Playback, Backup, Network Tive HD
Recording	Frame Rate		Adjustable Frame Rate for Each Camera
	Recording Mode		Manual, Schedule, Event(Motion, Sensor)
	Recording FPS	Max. 200/240fps	Max. 400/480fps
	Protect Video/Audio File		Protect Video/Audio from HDD Overwrite
	Still Image Capture		Live or Playback Image Local Capture and Backup for legal evidence
	Internal Hard Drive		SATA, Up to 4xHDDs(Max. 6TB Capacity)
Remote Monitoring/Control	External Hard Drive		e-SATA
	Remote View and Control via Gigabit Ethernet		Dynamic/Static/Zero Config Support
	Web Browsing, NC-Titanium, Tive		NAT Traversal Support
	Dual Streaming for Live and Recording		E-Map support
	E-Map support		
Playback	Playback Screen Mode	1/4/9/13	1/4/9/13/16
	Search Mode	Date/Time, Calendar, Event, Motion, Protect, Capture, VCA, Text	
Alarm Control	External Sensor Input	8CH NC/NO	16CH NC/NO
	Alarm Output		Buzzer, OSD, 4xRelay
Data Backup			2xUSB 2.0 Flash Memory
			AVI Format for Easy Viewing, Private Format for Image Authentication
Others	Video Content Analysis		Yes(with Specific Cameras)
	POS/ATM		Yes(with VSI/VSSI-Pro)
	NTP Server/Client		Yes
	System Keyboard		USB and Serial Support
	Printer		USB or Network Printer
	Control		IR Remote Control, USB Mouse, Client Software
	Event Log & Pre-Alarm Record		System/Event Log Management, Pre-Recording for Motion/Sensor
	Auto Deletion		Setup Recording Duration Per Channel
	Language		48 Languages Support
	Power Supply		48VDC, 3.1A
	Power Consumption		Max. 140W
	Operating Temperature		0~+45°C(+32~+113°F)
	Operating Humidity		0~ 90%RH
	Weight(Main Unit)		5.5kg without HDD
	Weight(Packing)		7kg without HDD
Dimension(Main Unit)		435x347x88mm(17x13.6x3.4 inch)	
Dimension(Packing)		550x475x220mm(21.6x18.7x8.6 inch)	

Specifications are subject to change without notice.

## Key Functions

- Quick Setup by Automatic Camera Detection and Setup Wizard&Zeroconfig
- Multiple Profile Recording(Schedule, Pre-Event, Text-In and Event)
- Alarm Handling with History Log and Pre-Alarm Recording
- Simultaneous 3 User Access(20 Users Registration)
- Text Input for POS.
- Network Time Synchronization
- S.M.A.R.T. Hard Disc Check
- Cross Web Browsing(IE, Safari, Firefox, Chrome)
- Dashboard


## Software

- SmartManager
- NC-Titanium
- Tive HD
- Titanium Plus VMS

## Optional Accessory

- HAS-02R / HAS-04R(e-SATA Storage)
- HAS-08I(iSCSI Storage)

## Dimension



Manufacturer by  
**HITRON INC.**

135-220, HITRON B/D 726-5, SUSEO-DONG, KANGNAM-GU, SEOUL, KOREA  
T : 02-3410-9330~1 / F : 02-459-7586 / E : inquiry@hitron.co.kr